Use nginx to serve static files from subdirectories of a given directory

Asked 12 years, 6 months ago Modified 9 months ago Viewed 280k times



I have several sets of static .html files on my server, and I would like use nginx to serve them directly. For example, nginx should serve an URI of the following pattern:

108



www.mysite.com/public/doc/foo/bar.html




with the .html file that is located at /home/www-data/mysite/public/doc/foo/bar.html. You can think of foo as the set name, and bar as the file name here.



I wonder whether the following piece of nginx config would do the job:

```
server {
   listen
                  8080;
    server_name
                 www.mysite.com mysite.com;
    error_log
                  /home/www-data/logs/nginx_www.error.log;
                         /404.html;
   error_page
    location /public/doc/ {
        autoindex
                          on;
        alias
                          /home/www-data/mysite/public/doc/;
    }
    location = /404.html {
                          /home/www-data/mysite/static/html/404.html;
        alias
```



.../....html are going to be handled by yesite.com/404.html is returned.

asked Oct 9, 2012 at 19:17

MLister

10.3k • 18 • 67 • 93

orted by: Highest score (default)

<u>mapmg</u>x http core module.html#alias says:



147

When location matches the last part of the directive's value: it is better to use the root directive instead:



which would yield:







```
server {
 listen
               8080;
  server_name www.mysite.com mysite.com;
               /home/www-data/logs/nginx_www.error.log;
 error_log
                      /404.html;
 error_page
 location /public/doc/ {
    autoindex on;
    root /home/www-data/mysite;
 }
 location = /404.html {
    root /home/www-data/mysite/static/html;
 }
}
```


Share Improve this answer Follow



answered Oct 9, 2012 at 19:43



- 1 Using 2 roots gave me problems in the past, what I usually do is use one root and alias for other locations as @AlessioCampanelli suggests - camposer Apr 11, 2020 at 11:42 🖍
- 1 Using root is the right answer. However it does not serve the static pages for me. bsesic Oct 12, 2022 at 6:10





You can use the following code. You can also use this code to serve vuejs or reactjs static files, Just modifile the alias to point to the root of your file directory;





location /files {
 #autoindex on;
 alias /files;
 try_files \$uri /index.html =404;
}

43

Make sure the access permissions are right too. sudo chown -R 1000 /files

Example on how to access the files http://example.com/files/text-file.txt

Share Improve this answer Follow

edited Apr 1, 2023 at 11:05

answered Mar 17, 2023 at 8:18






if you are using static middleware for example app.use(express.static('assets'));

suppose you have an image in yourprojectAddress/assets/media/cat1.jpg and you are using port 3000 for your application



so to serve that image this is nginx config

location /media/ {



Explore related questions

nginx

static-files

See similar questions with these tags.

